

ULIC GAT

- Strahler auf 3-Phasen-Universaladapter aus Aluminiumdruckguß
 - Philips Chip Fortimo SLM Gen.5, Food Bäckerei oder Food Metzgerei
 - Pulverbeschichtet in weiß, schwarz, silber sowie RAL auf Anfrage
 - Hocheffiziente Reflektoren aus 99,9 % Reinstaluminium wahlweise in 16, 24, 36 oder 60°
 - Bajonettfrontring mit klarem Schutzglas für werkzeuglosen Reflektorwechsel, das Schutzglas schützt Chip und Reflektor vor Verunreinigungen
 - Inkl. Standarttreiber, dimmbare Treiber auf Anfrage
 - PASSIVE Kühlung
 - 350° dreh- und 90° schwenkbar
 - Gewicht NUR 0,95 kg
-
- Projector with 3-phase-uniadapter made out of aluminium-diecast
 - Philips Chip Fortimo SLM Gen.5, Food Bäckerei or Metzgerei
 - Powderpainted in white, black, silver or in RAL upon demand
 - High efficient reflectors out of extra pure aluminium 99,9 % optionally with beamangle 16, 24, 36 or 60°
 - Twist & look frontring for change of glass & reflectors without any tools, the clear glass protects chip & reflector from dust & dirt
 - Incl. standartdriver, dimmable driver upon demand
 - PASSIVE cooling
 - 350° turnable & 90° adjustable
 - Weight 0,95 kg ONLY!



F **CE IP 20** 220 - 240 V
50 - 60 Hz

- | | | |
|-------------------------------|-------------------------------|----------------------------|
| 1
 | 2
 | 3
 |
| RAL 9006
silber/
silver | RAL 9005
schwarz/
black | RAL 9016
weiß/
white |

Fortimo SLM Gen.5 LES 19mm 25-33 W

830	3.000 K	RA 80	3.420 - 4.160 Lumen
835	3.500 K	RA 80	3.540 - 4.340 Lumen
840	4.000 K	RA 80	3.650 - 4.480 Lumen
927	2.700 K	RA 90	2.820 - 3.460 Lumen
930	3.000 K	RA 90	2.970 - 3.620 Lumen



Food Spezial Bäckerei

1.560 - 1.790 Lumen 2.400 K

Food Spezial Metzgerei

1.290 - 1.500 Lumen



2112

16°	2112-_-16
24°	2112-_-24
36°	2112-_-36
60°	2112-_-60